



CRF150R/Expert



Getting the holeshot is the first, critical step to winning a race. And the same goes with choosing a racer's bike. That's why we build the CRF*150R and CRF150R Expert. These motocrossers are like giving a young rider a career holeshot—an advantage right from the start. Built around a high-performance Unicam* engine inspired by our open-class CRF450R, they provide a wide powerband without needing a ton of maintenance. And because winners come in all sizes, we offer two versions, both freshened up with new graphics this year to keep your young Red Rider looking like a winner too: Our Expert model uses the same great engine, but features bigger wheels, a longer swingarm and higher seat to better suit taller riders. Choose your weapon, and then get ready to win!





CRF150R/EXPERT IS INTENDED FOR CLOSED-COURSE OPERATION ONLY. ALWAYS WEAR A HELMET, EYE PROTECTION AND PROTECTIV CLOTHING, AND PLEASE RESPECT THE ENVIRONMENT. OBEY THE LAW AND READ THE OWNER'S MANUAL THOROUGHLY. Showa® is a registered trademark of Showa Mfg., Inc. CRF®, Pro-Link® and Unicam® are registered trademarks of Honda Motor Co., Ltd. ©2021 Americal Honda Co., Inc.



Life is better on a Honda

2022 CRF150R/Expert





SPECIFICATIONS

ENGINE TYPE — 149.8cc liquid-cooled single cylinder four stroke

BORE AND STROKE – 66mm x 43.7mm

COMPRESSION RATIO - 11.7:1

VALVE TRAIN
Unicam, four-valve; 26mm intake, steel; 22.5mm exhaust, steel

Keihin 32mm flat slide with Throttle Position Sensor (TPS)

IGNITION - AC-CDI

TRANSMISSION - Close-ratio five speed

FINAL DRIVE – #420 chain; 15T/50T, Expert 15T/56T

FRONT SUSPENSION — 37mm fully adjustable leading-axle inverted Showa cartridge fork; 9.5

inches of travel

Pro-Link® fully adjustable Showa® single shock; 10.7 inches of travel,

Expert 11.1 inches of travel

FRONT BRAKE – Single 220mm hydraulic disc

REAR BRAKE – Single 190mm hydraulic disc

FRONT TIRE - 70/100-17 Dunlop MX51, Expert 70/100-19 Dunlop MX51

REAR TIRE — 90/100-14 Dunlop MX51, Expert 90/100-16 Dunlop MX51

RAKE — (Caster Angle) 27° 2′, Expert 27° 48′

TRAIL - 3.1 inches, Expert 3.8 inches

WHEELBASE - 49.6 inches, Expert 50.6 inches

SEAT HEIGHT - 32.8 inches, Expert 34.1 inches

GROUND CLEARANCE – 11.9 inches, Expert 13.2 inches

CURB WEIGHT – 185 pounds, Expert 187 pounds (Includes all standard equipment,

required fluids and full tank of fuel-ready to ride.)

FUEL CAPACITY – 1.11 gallons

FEATURES & BENEFITS



UNICAM ENGINE

The CRF150R uses a Unicam engine based on our championship-winning CRF450R. Designed to give you excellent rideability and more power and torque across the rev range, the engine runs consistently at different tracks—it's an all-around winner.



ACCELERATOR PUMP

The CRF150R uses a carburetor featuring a "direct push" accelerator pump which gives you better, more immediate throttle response.



TRACK-DESIGNED CHASSIS

A lightweight, high-tensile steel frame with large-diameter frame tubing and crossmember delivers excellent turning performance and straight-line tracking.



FRONT DISC BRAKE

The front disc brake provides powerful, precise braking.